

Pixel-wise uncertainty quantification in electric properties tomography

Arduino Alessandro¹, Stefano Mandija^{2,3}, Francesca Pennechi¹,
Cornelis A. T. van den Berg^{2,3}, Luca Zilberti¹

¹Istituto Nazionale di Ricerca Metrologica (INRiM), Torino, Italy

²Department of Radiotherapy, University Medical Center Utrecht, Utrecht, Netherlands


³Computational Imaging Group for MR Diagnostics & Therapy, Center for Image Sciences, University Medical Center Utrecht, Utrecht, Netherlands



Work developed in the framework of the Project **18HLT05 "QUIERO"**. This project has received funding from the EMPIR programme co-financed by the Participating States and from the European Union's Horizon 2020 research and innovation programme.

Introduction


- **Electric Properties Tomography (EPT)** images the electric properties (EPs) of biological tissues



Introduction


- **Electric Properties Tomography** (EPT) images the electric properties (EPs) of biological tissues
- EPT is based on **Magnetic Resonance Imaging** (MRI) for the input maps

Static field	Larmor frequency
1.5 T	64 MHz
3 T	128 MHz
7 T	300 MHz



Introduction


- EPs in the radiofrequency (RF) range can act as **physical biomarkers**




Van Lier et al., Proc. ISMRM p.4464, 2011

Introduction

- EPs in the radiofrequency (RF) range can act as **physical biomarkers**
- Knowing the value of tissue EPs is very important for accurate **numerical simulations**




Van Lier et al., Proc. ISMRM p.4464, 2011



Kok et al., Radiation Oncology 10:196, 2015

Introduction

- A **plethora of techniques** for EPT are proposed in the literature
- Each one with its own **model errors**



Introduction

- A **plethora of techniques** for EPT are proposed in the literature
- Each one with its own **model errors**

OBJECTIVE

To estimate the **pixel-wise uncertainty** of the retrieved EPs maps taking into account the model errors.

Introduction

- A **plethora of techniques** for EPT are proposed in the literature
- Each one with its own **model errors**

OBJECTIVE


To estimate the **pixel-wise uncertainty** of the retrieved EPs maps taking into account the model errors.

- This would allow us to **compare** the EPT results

Method

- **Phase-based Helmholtz-EPT** consists in the evaluation of a Laplacian

$$\sigma = \frac{\nabla^2 \varphi^\pm}{2\omega\mu_0}$$




Method

- **Phase-based Helmholtz-EPT** consists in the evaluation of a Laplacian

$$\sigma = \frac{\nabla^2 \varphi^\pm}{2\omega\mu_0}$$

- The Laplacian is evaluated through the **Savitzky–Golay filter**:
 1. A moving kernel is centered at the pixel of interest
 2. The phase map is locally approximated with a polynomial fitting
 3. The Laplacian of the polynomial is evaluated analytically




Method

- Phase-based Helmholtz-EPT consists in the evaluation of a Laplacian

$$\sigma = \frac{\nabla^2 \varphi^\pm}{2\omega\mu_0}$$

- The Laplacian is evaluated through the **Savitzky–Golay filter**:
 - A moving kernel is centered at the pixel of interest
 - The phase map is locally approximated with a polynomial fitting
 - The Laplacian of the polynomial is evaluated analytically

$$\mathbf{x}^* = \operatorname{argmin}_{\mathbf{x} \in \mathbb{R}^n} \|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2, \quad \mathbf{A} \in \mathbb{R}^{m,n}, \mathbf{b} \in \mathbb{R}^m$$



Method

$$\mathbf{x}^* = \operatorname{argmin}_{\mathbf{x} \in \mathbb{R}^n} \|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2$$

- The **QR decomposition** of \mathbf{A} allows to:
 1. Solve the problem
 2. Estimate the uncertainty of \mathbf{x}^*

Method

$$\mathbf{x}^* = \operatorname{argmin}_{\mathbf{x} \in \mathbb{R}^n} \|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2$$

- The **QR decomposition** of A allows to:
 1. Solve the problem
 2. Estimate the uncertainty of \mathbf{x}^*

- $Q \in \mathbb{R}^{m,m}$ is an orthogonal matrix
- $R \in \mathbb{R}^{m,n}$ is an upper triangular matrix, $R = \begin{pmatrix} \tilde{R} \\ 0 \end{pmatrix}$
- $A = QR$

Method

$$\mathbf{x}^* = \operatorname{argmin}_{\mathbf{x} \in \mathbb{R}^n} \|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2$$

- The **QR decomposition** of \mathbf{A} allows to:
 1. Solve the problem
 2. Estimate the uncertainty of \mathbf{x}^*

- $\mathbf{Q} \in \mathbb{R}^{m,m}$ is an orthogonal matrix
- $\mathbf{R} \in \mathbb{R}^{m,n}$ is an upper triangular matrix, $\mathbf{R} = \begin{pmatrix} \tilde{\mathbf{R}} \\ \mathbf{0} \end{pmatrix}$
- $\mathbf{A} = \mathbf{Q}\mathbf{R}$

$$\|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2 = \|\mathbf{R}\mathbf{x} - \underbrace{\mathbf{Q}^T \mathbf{b}}_{\mathbf{c}}\|^2 = \left\| \begin{pmatrix} \tilde{\mathbf{R}}\mathbf{x} - \mathbf{c}_1 \\ \mathbf{c}_2 \end{pmatrix} \right\|^2 = \|\tilde{\mathbf{R}}\mathbf{x} - \mathbf{c}_1\|^2 + \|\mathbf{c}_2\|^2$$

Method

$$\mathbf{x}^* = \operatorname{argmin}_{\mathbf{x} \in \mathbb{R}^n} \|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2$$

- The **QR decomposition** of \mathbf{A} allows to:
 1. Solve the problem
 2. Estimate the uncertainty of \mathbf{x}^*

- $\mathbf{Q} \in \mathbb{R}^{m,m}$ is an orthogonal matrix
- $\mathbf{R} \in \mathbb{R}^{m,n}$ is an upper triangular matrix, $\mathbf{R} = \begin{pmatrix} \tilde{\mathbf{R}} \\ \mathbf{0} \end{pmatrix}$
- $\mathbf{A} = \mathbf{Q}\mathbf{R}$

$$\|\mathbf{A}\mathbf{x} - \mathbf{b}\|^2 = \|\mathbf{R}\mathbf{x} - \underbrace{\mathbf{Q}^T \mathbf{b}}_{\mathbf{c}}\|^2 = \left\| \begin{pmatrix} \tilde{\mathbf{R}}\mathbf{x} - \mathbf{c}_1 \\ \mathbf{c}_2 \end{pmatrix} \right\|^2 = \|\tilde{\mathbf{R}}\mathbf{x} - \mathbf{c}_1\|^2 + \|\mathbf{c}_2\|^2$$

$$\mathbf{x}^* = \tilde{\mathbf{R}}^{-1} \mathbf{c}_1$$

$$\chi_n^2 = \frac{\|\mathbf{c}_2\|^2}{m - n}$$

Method

- χ_n^2 estimates the variance of \mathbf{b} components, assumed to be independent identically distributed

$$\Sigma(\mathbf{b}) = \chi_n^2 I \quad \Rightarrow \quad \Sigma(\mathbf{c}) = Q^T \Sigma(\mathbf{b}) Q = \chi_n^2 (Q^T Q) = \chi_n^2 I$$

Method

- χ_n^2 estimates the variance of \mathbf{b} components, assumed to be **independent identically distributed**

$$\Sigma(\mathbf{b}) = \chi_n^2 I \quad \Rightarrow \quad \Sigma(\mathbf{c}) = Q^T \Sigma(\mathbf{b}) Q = \chi_n^2 (Q^T Q) = \chi_n^2 I$$

- The **law of propagation of the uncertainty** can be used again

$$\Sigma(\mathbf{x}^*) = \tilde{R}^{-1} \Sigma(\mathbf{c}_1) \tilde{R}^{-T} = \chi_n^2 \tilde{R}^{-1} \tilde{R}^{-T}$$

Method

- χ_n^2 estimates the variance of \mathbf{b} components, assumed to be **independent identically distributed**

$$\Sigma(\mathbf{b}) = \chi_n^2 I \quad \Rightarrow \quad \Sigma(\mathbf{c}) = Q^T \Sigma(\mathbf{b}) Q = \chi_n^2 (Q^T Q) = \chi_n^2 I$$

- The **law of propagation of the uncertainty** can be used again


$$\Sigma(\mathbf{x}^*) = \tilde{R}^{-1} \Sigma(\mathbf{c}_1) \tilde{R}^{-T} = \chi_n^2 \tilde{R}^{-1} \tilde{R}^{-T}$$

- Finally, the Laplacian is computed as a **linear combination** of the polynomial coefficients

$$\sigma = \mathbf{w}^T \mathbf{x}^* \quad \Rightarrow \quad u(\sigma)^2 = \mathbf{w}^T \Sigma(\mathbf{x}^*) \mathbf{w} = \chi_n^2 (\tilde{R}^{-T} \mathbf{w})^T (\tilde{R}^{-T} \mathbf{w}) = \chi_n^2 \|\tilde{R}^{-T} \mathbf{w}\|^2$$

Application to phantom measurements


- φ^{\pm} acquired by a 3 T MRI scanner (Ingénia, Philips HealthCare, Best, The Netherlands)
 - Body coil in transmit mode
 - 15-channel head coil in receive mode



Region	Radius [cm]	σ [S/m]
r1	6.25	0.1
r2	2	1
r3	2	2
r4	2	4

Application to phantom measurements


- φ^{\pm} acquired by a 3 T MRI scanner (Ingénia, Philips HealthCare, Best, The Netherlands)
 - Body coil in transmit mode
 - 15-channel head coil in receive mode
- Two T1-weighted Spin-Echo maps acquired with opposite readout polarities and combined for the φ^{\pm} acquisition
 - TR = 900 ms; TE = 5 ms; resolution = 2 mm isotropic



Region	Radius [cm]	σ [S/m]
r1	6.25	0.1
r2	2	1
r3	2	2
r4	2	4

Application to phantom measurements


- φ^{\pm} acquired by a 3 T MRI scanner (Ingénia, Philips HealthCare, Best, The Netherlands)
 - Body coil in transmit mode
 - 15-channel head coil in receive mode
- Two T1-weighted Spin-Echo maps acquired with opposite readout polarities and combined for the φ^{\pm} acquisition
 - TR = 900 ms; TE = 5 ms; resolution = 2 mm isotropic
- Agar-based (2 %) phantom with inner compartments with NaCl added.



Region	Radius [cm]	σ [S/m]
r1	6.25	0.1
r2	2	1
r3	2	2
r4	2	4


Application to phantom measurements

- The kernels of the Savitzky-Golay filter are square of $2n + 1$ pixels per edge
- Large uncertainties at **compartment boundaries** → Model errors are included




Application to phantom measurements

- The maps can be **compared** and **combined** pixel-by-pixel looking for:
 - Minimum uncertainty
 - Positive conductivity (physical constraint)
- Highlighted the regions where the relative uncertainty $u(\sigma)/\sigma$ is below 1



Application to phantom measurements

- The maps can be **compared** and **combined** pixel-by-pixel looking for:
 - Minimum uncertainty
 - Positive conductivity (physical constraint)
- Highlighted the regions where the relative uncertainty $u(\sigma)/\sigma$ is below 1





Hybridization of EPT techniques

- Phase-based **convection reaction-EPT** is a technique based on a PDE

$$\nabla \cdot (\rho \nabla \varphi^\pm) = 2\omega\mu_0$$

- Once discretized, it can be written as a **least squares problem**
- The problem can be **regularized** with a weighted additive term derived by the Helmholtz-EPT solution




Hybridization of EPT techniques

- Phase-based **convection reaction-EPT** is a technique based on a PDE


$$\nabla \cdot (\rho \nabla \varphi^\pm) = 2\omega\mu_0$$

- Once discretized, it can be written as a **least squares problem**
- The problem can be **regularized** with a weighted additive term derived by the Helmholtz-EPT solution
- Using the QR decomposition the problem can be solved obtaining also the uncertainty map.


Convection reaction-EPT




Helmholtz-EPT



Hybrid-EPT



Relative uncertainty (%)



Conclusions

- A pixel-wise estimation of the uncertainty in Helmholtz-EPT has been presented
- The procedure can be applied also to other techniques based on the least squares problem
- Such an uncertainty estimation is fundamental for:
 - Quantitative pixel-wise comparison
 - Weighted hybridization of EPT techniques

Conclusions

- A pixel-wise estimation of the uncertainty in Helmholtz-EPT has been presented
- The procedure can be applied also to other techniques based on the least squares problem
- Such an uncertainty estimation is fundamental for:
 - Quantitative pixel-wise comparison
 - Weighted hybridization of EPT techniques

Thank you for your attention!